

Chartpak, Inc.  
 One River Road  
 Leeds, MA 01053  
 Phone: 413-584-5446 or 800-628-1910

**Emergency Medical Number: Poison Control 800-222-1222**  
**Emergency Transport Number: Chemtrec 800-424-9300**  
 or (01) 703-527-3887 (CCN4391)

**General Inquiry Number: Chartpak 413-584-5446**  
**Date: November 4, 2011**

**Section One: Product Information**

Product Name: Grumbacher Pre-Tested Odorless Thinner  
 Product Sizes: 2.5 oz., 8 oz., 16 oz., 32 oz.  
 Product Class: Mediums

**Section Two: Ingredients**

Ingredients	CAS Number	% by Weight	PEL/TLV
Petroleum Distillates	64742-48-9	100%	N/A

**Section Three: Hazards Identification**

WARNING: COMBUSTIBLE. HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. MAY BE HARMFUL IF SWALLOWED.  
 CONTAINS: PETROLEUM DISTILLATES  
 KEEP OUT OF REACH OF CHILDREN.

**Section Four: First Aid Measures**

Inhalation: Move to fresh air.  
 Skin Contact: Wash with soap and water.  
 Eye Contact: Flush with flowing water.  
 Ingestion: If swallowed, do not induce vomiting. Call a physician or poison control center immediately. For further health information, contact a poison control center.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: 5652, 5658, 56516, 56532

**Section Five: Fire Fighting Measures**

Flash Point: 129F

Flammability Limits (% by volume): Lower: Not explosive Upper: Not explosive

Extinguishing Media: No special media required.

Special Fire Fighting Measures: No special fire fighting procedures required.

Unusual Fire and Explosion Hazards: Combustible

**Section Six: Accidental Release Measures**

Wipe up with absorbent material.

**Section Seven: Handling and Storage**

Handling: Assure adequate cross ventilation.

Storage: Do not store or use near heat or flame.

**Section Eight: Exposure Controls and Personal Protection**

Respiratory Protection and Special Ventilation Requirements: Use exhaust fan to assure adequate cross ventilation.

Other Protective Equipment (Gloves, Goggles, Etc.): Rubber gloves and eye protection recommended.

Work/Hygiene Practices: PRECAUTIONS: Avoid ingestion. Do not store or use near heat or flame. Use only with adequate ventilation.

**Section Nine: Physical and Chemical Properties**

Boiling Point: 345F Melting Point: Not determined

Vapor Pressure: 10 mm Hg Specific Gravity: 0.76

Specific Vapor Density (AIR = 1): >5 Evaporation Rate (Butyl Acetate = 1): Slower

Solubility in Water: Negligible Reactivity in Water: Non-reactive

Appearance and Odor: Clear liquid; oily odor

**Section Ten: Stability and Reactivity**

Stability: Stable

Conditions to Avoid: Excessive heat

Chemical Incompatibility: None known

Hazardous Decomposition: None known

Hazardous Polymerization: Will not occur

**Section Eleven: Toxicological Information**

IARC Monographs: No  
 National Toxicology Program: No  
 OSHA Regulated: No  
 Effects/Symptoms of Acute Exposure: Irritation of the eyes or chest.  
 Effects/Symptoms of Chronic Exposure: None expected  
 Medical Conditions Usually Aggravated By Overexposure of This Product: Unknown

**Section Twelve: Ecological Information**

Not available

**Section Thirteen: Disposal Considerations**

Dispose in accordance with Federal, State, and Local Regulations

**Section Fourteen: Transport Information**

ORM-D Consumer Commodity  
 Flammable Liquid, n.o.s. (Petroleum Distillates), 3, UN1993, III (120°F TCC/ 48.8 °C), Ltd Qtys, EmS# F-E, S-E  
 Consumer Commodity, 9, ID8000, packing instruction 910

**Section Fifteen: Regulatory Information**

TSCA INVENTORY:  
 The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

**Section Sixteen: Other Information**

HMIS Code	
Health	2
Flammability	2
Reactivity	0
Personal Protection	B

Chartpak, Inc. is a member of the Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the CL (Cautionary Label) Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236.

**0=Minimal / 4 = Severe**

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.