MATERIAL SAFETY DATA SHEET

Page 1 of 3

Chartpak, Inc. One River Road Leeds, MA 01053 Phone: 413-584-5446 or 800-628-1910

Emergency Medical Number: Poison Control 800-222-1222 Emergency Transport Number: Chemtrec 800-424-9300 or (01) 703-527-3887 (CCN4391)

General Inquiry Number: Chartpak 413-584-5446 Date: November 4, 2011

Section One:	Product Information	
Product Name:	Grumbacher Stand Oil	
Product Sizes:	2.5 oz.	
Product Class: Me	diums	
Section Two:	Ingredients	

	Ingredients				
Ingredients		CAS Number	% by Weight	PEL/TLV	
Linseed Oil		8001-26-1	100%	N/A	

Section Three:

Hazards Identification

This product is considered safe under normal use conditions.

Section Four:	First Aid Measures
Inhalation:	None under normal use conditions.
Skin Contact:	None under normal use conditions.
Eye Contact:	None under normal use conditions.
Ingestion:	None under normal use conditions.

This Material Safety Data Sheet is applicable to the consumer use of the following colors: 5662

MATERIAL SAFETY DATA SHEET

MSDS #: 566

Page 2 of 3

Section Five: Fi	re Fighting Measures
Flash Point:	>200F
Flammability Limits (% by volume)	: Lower: Not explosive Upper: Not explosive
Extinguishing Media:	Foam, carbon dioxide, dry chemical
Special Fire Fighting Measures:	Firefighters should wear self-contained breathing apparatus to prevent inhalation of smoke or vapors.
Unusual Fire and Explosion Hazards:	None known

Section Six: Accidental Release Measures
--

Wipe up with absorbent material.

Section Seven:	На	ndling and Storage
Handling:	No special handling requirements.	
Storage:	No special	storage requirements.
Section Eight:		Exposure Controls and Personal Protection
Respiratory Protect Special Ventilation		None required
Other Protective E (Gloves, Goggles,		Eye protection and gloves are recommended.
Work/Hygiene Pra	ictices:	DANGER: RAGS, STEEL WOOL, OR WASTE SOAKED WITH THIS PRODUCT MAY SPONTANEOUSLY CATCH FIRE IF IMPROPERLY DISCARDED. CONTAINS: OXIDIZING OIL. PRECAUTIONS: Immediately after use, place soiled material in a sealed water-filled metal container.

Section Nine:	Physical and Chemical Prop	erties	
Boiling Point:	600F	Melting Point:	Not determined
Vapor Pressure:	Not determined	Specific Gravity:	0.97
Specific Vapor Density (A	AIR = 1): Heavier than air	Evaporation Rate (But	yl Acetate = 1): Slowe
Solubility in Water:	Negligible	Reactivity in Water:	Non-reactive
Appearance and Odor:	Pale liquid; oily odor		

Section Ten:	Stability and Reactivity
Stability:	Stable
Conditions to Avoid:	Extreme heat
Chemical Incompatibility:	None known
Hazardous Decomposition:	Thermal decomposition may yield carbon monoxide, carbon dioxide, and sooty smoke.
Hazardous Polymerization:	Will not occur

MATERIAL SAFETY DATA SHEET

MSDS #: 566

Page 3 of 3

Section Eleven:	Toxicological Information
IARC Monographs:	No
National Toxicology Pro	ogram: No
OSHA Regulated:	No
Effects/Symptoms of Acute Exposure:	Excessive inhalation may affect the respiratory system.
Effects/Symptoms of Chronic Exposure:	Dermatitis
Medical Conditions Use Aggravated By Overex of This Product:	bosure
Section Twelve:	Ecological Information
Not available	
Section Thirteen:	Disposal Considerations
PRECAUTIONS: Imm Federal, State, and Loc	ediately after use, placed soiled material in a sealed water-filled metal container. Dispose in accordance with al Regulations.
Section Fourteen:	Transport Information
	ardous material by DOT, IMO, or IATA.

Section Fifteen:	Regulatory Information

TSCA INVENTORY:

The product on this Material Safety Data Sheet is not listed on the United States Environmental Protection Agency Toxic Substances Control Act Inventory. However, the components of the product are included in the TSCA Inventory.

Section Sixteen:	Other Information	
HMIS Code		
Health 0	Chartpak, Inc. is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the AP Nontoxic Seal. Products bearing the AF	
Flammability 1	Approved Product Seal of The Art and Creative Materials Institute, Inc. are certified in a program o toxicological evaluation by a medical expert, subject to the approval of the Institute Toxicological	
Reactivity 0	Advisory Board, to contain no materials in sufficient quantities to be toxic or injurious to humans, or to cause acute or chronic health problems.	
Personal Protection B		

0=Minimal / 4 = Severe

May be used to comply with OSHA Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements.